

18**TEST
LATHE SAFETY**NAME: _____
CLASS OR PERIOD: _____
DATE: _____ SCORE: _____**ALWAYS WEAR EYE PROTECTION**

1. A _____ should be worn to protect your eyes when operating a lathe.
2. _____ should be tucked neatly under a cap to keep it from being caught in the moving lathe.
3. Loose clothing must be tucked in neatly so it won't get _____ in the lathe.
4. Never wear a necklace or other _____ while operating the lathe.
5. No one should stand near the operator or _____ to the person operating the lathe.
6. When a safety shield is used, it must be kept _____ so the operator can see through it clearly.
7. The wood that is being turned must be in good condition and free of any _____.
8. If the wood has been glued, it should set up for at least 24 hours and be firmly _____ before it is turned.
9. When the dead center is used, it should be _____ to reduce friction.
10. The material must be _____ and fastened firmly in the lathe.
11. Adjust the tool rest so it is close to the material without _____ it at any point.
12. The wood turning chisels and gouges must be in good condition and _____.
13. Use only chisels and gouges that are specifically designed and manufactured for _____.

**COMPLETE EACH STATEMENT
WITH THE CORRECT LETTER
OR WORDS IN THIS COLUMN**

- A. WOOD TURNING
- B. ADJUSTMENTS
- C. MIDDLE
- D. SCRAPING
- E. POLISHING RAG
- F. TOUCHING
- G. LUBRICATED
- H. FACE SHIELD
- I. JEWELRY
- J. DEFECTS
- K. SLOW
- L. MOUNTING SCREWS
- M. DEEP
- N. DANGEROUS
- O. LONG HAIR
- P. TALK
- Q. BONDED
- R. CENTERED
- S. SPEED
- T. UNDERSTAND
- U. TOOL REST
- V. SHARP
- W. VIBRATE
- X. FIRMLY
- Y. FACEPLATE
- Z. CAUGHT
- AA. CLEAN



NAME: _____

CLASS OR PERIOD: _____

14. The _____ of the lathe should be adjusted for the type of material and the size of the material that is going to be turned.
15. The lathe should be turned off immediately if it begins to _____.
16. The lathe must be turned off and completely stopped before any _____ or measurements are made.
17. Dull tools are more _____ than tools that are kept sharp.
18. The cutting tool must be held _____ with both hands.
19. Whenever possible, the cut should be started in the _____ of the stock.
20. The cut should be shallow, smooth and even. A cut that is too _____ is dangerous.
1. When faceplate turning, the material must be securely fastened to the _____.
2. A _____ type of cut must be used for faceplate turning.
3. When _____ are used to hold the material to the faceplate, extra care must be taken to avoid cutting into them.
4. Before any sanding or polishing operation, the _____ must be removed.
5. Fold the _____ neatly so it won't get caught in the turning lathe or the material.
6. Use a _____ speed for sanding or polishing.
7. Do not use the lathe until you fully _____ how to use it correctly and safely.

- A. WOOD TURNING
- B. ADJUSTMENTS
- C. MIDDLE
- D. SCRAPING
- E. POLISHING RAG
- F. TOUCHING
- G. LUBRICATED
- H. FACE SHIELD
- I. JEWELRY
- J. DEFECTS
- K. SLOW
- L. MOUNTING SCREWS
- M. DEEP
- N. DANGEROUS
- O. LONG HAIR
- P. TALK
- Q. BONDED
- R. CENTERED
- S. SPEED
- T. UNDERSTAND
- U. TOOL REST
- V. SHARP
- W. VIBRATE
- X. FIRMLY
- Y. FACEPLATE
- Z. CAUGHT
- AA. CLEAN